

Product Range

Type No.	NOMINAL CAPACITY					Kilo-Watt Hours (120 HRS)	Poles	MECHANICAL CHARACTERISTICS							
	240 HR	120 HR	100 HR	20 HR	10 HR			Length		Width		Height*		Weight	
	1.85VPC at 20°C / 68°F			1.75VPC at 27°C / 80°F				IN	MM	IN	MM	IN	MM	LB	KG
2 VOLT CELLS															
2VRE-400TF	197	187	183	139	126	0.37	2	4.1	103	8.1	206	15.0	380	30	14
2VRE-500TF	274	263	258	198	180	0.53	2	4.1	103	8.1	206	15.0	380	35	16
2VRE-600TF	310	300	294	237	215	0.60	2	4.1	103	8.1	206	15.0	380	39	18
2VRE-800TF	391	378	370	297	270	0.76	2	4.9	124	8.1	206	15.0	380	47	21
2VRE-900TF	470	454	445	356	324	0.91	2	5.7	145	8.1	206	15.0	380	57	26
2VRE-1100TF	574	553	542	436	396	1.11	2	4.9	124	8.1	206	19.5	496	63	28
2VRE-1300TF	686	661	648	521	474	1.32	2	5.7	145	8.1	206	19.5	496	74	34
2VRE-1500TF	780	750	735	595	541	1.50	2	6.5	166	8.1	206	19.5	496	85	39
2VRE-1800TF	948	904	886	670	609	1.81	2	5.7	145	8.1	206	26.4	671	93	42
2VRE-2000TF	1006	966	947	739	672	1.93	2	5.7	145	8.1	206	26.4	671	101	46
2VRE-2500TF	1286	1230	1205	920	836	2.46	4	7.5	191	8.3	210	26.4	671	132	60
2VRE-2600TF	1330	1278	1252	982	893	2.56	4	7.5	191	8.3	210	26.4	671	141	64
2VRE-3000TF	1546	1484	1454	1131	1028	2.97	4	9.2	233	8.3	210	26.4	671	161	73
2VRE-3200TF	1656	1592	1560	1225	1114	3.18	4	9.2	233	8.3	210	26.4	671	172	78
2VRE-3800TF	1985	1908	1870	1462	1329	3.82	4	10.8	275	8.3	210	26.4	671	201	91
2VRE-4400TF	2283	2216	2172	1785	1623	4.43	4	10.8	275	8.3	210	32.3	821	244	111
2VRE-4500TF	2294	2226	2181	1793	1630	4.45	4	10.8	275	8.3	210	32.3	821	254	115
2VRE-5500TF	2868	2770	2715	2176	1978	5.54	6	15.6	397	8.3	212	31.4	797	316	143
2VRE-5800TF	3019	2921	2863	2325	2114	5.84	6	15.6	397	8.3	212	31.4	797	328	149
2VRE-5900TF	3065	2972	2913	2405	2186	5.94	6	15.6	397	8.3	212	31.4	797	341	155
2VRE-7600TF	3917	3780	3704	2958	2689	7.56	8	19.2	487	8.3	212	31.4	797	406	184
2VRE-8200TF	4217	4076	3994	3219	2926	8.15	8	19.2	487	8.3	212	31.4	797	443	201
2VRE-9200TF	4769	4620	4528	3697	3361	9.24	8	22.7	576	8.3	212	31.4	797	507	230
6 & 12 VOLT BLOCKS															
6VRE-1500TF	252	242	237	195	177	1.45	2	9.2	233	8.8	224	14.9	378	91	41
6VRE-1700TF	293	283	277	237	215	1.70	2	10.7	272	8.1	205	14.3	363	104	47
6VRE-2300TF	403	389	381	316	287	2.33	2	15.0	380	8.1	205	14.3	363	134	61
6VRE-2400TF	422	408	400	343	312	2.45	2	15.0	380	8.1	205	14.3	363	148	67
12VRE-1000TF	91	86	84	69	63	1.03	2	10.7	272	8.1	205	14.3	363	83	38
12VRE-1600TF	137	132	129	113	103	1.58	2	10.7	272	8.1	205	26.1	363	109	49
12VRE-2300TF	199	191	187	165	150	2.29	2	15.0	380	8.1	205	14.3	363	154	70

*Includes installed connectors and shrouds.

Drawings

